HDPE dimpled membrane as part of drainage systems

Application
Drain Type 20 is used as a drainage membrane.

Properties
Drain Type 20 has a superior drainage capacity thanks to its studs design that is 20 mm high. The membrane is easy to install and can withstand humidity, soil, roots and frost.

Directions
Drain Type 20 is mainly used as floor drainage as part of a complete drainage system.

Technical characteristics

Structure	Stud height	20 mm
	Membrane	High density polyethylene
Colour	Black	
Total weight	+/- 1000 g/m²	
Stud count	+/- 400/m²	
Air volume between the studs	+/- 14 ltr/m²	
Compression strength	+/- 150 kN/m²	
Drainage capacity	+/- 10 ltr/s/m	
Temperature resistance	-40°C to +80°C	
Special features	Suitable for contact with food and drinking water	

Quantity to use
1 m²/1 m² (make sure you calculate some margin)

Packaging
Roll of 20 m of length, 2 m high

Safety information – Transport – Handling and storage - Waste
Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Considerations
The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.