

# Polishing compound for (transparent) glass

### **Application**

**Glaspolijstpasta** is used to remove deposits and lime scale, among others, from glass by polishing the surface.

#### **Properties**

**Glaspolijstpasta** is a polishing paste made of acid components and specially developed polishing granules.

#### **Directions**

**Preparation** 

Clean the glass surface with water in order to remove superficial soil, dust and sand. Shake **Glaspolijstpasta** well before use.

#### Work method

Apply a generous amount of **Glaspolijstpasta** to the glass surface and distribute the product by means of a polishing machine and the accessory polishing pad. If the glass surface is heavily stained or damaged, start with a rotational speed of 600 to 700 and slowly increase the speed up to a maximum of approximately 1,100 rotations. Use a large amount of water to clean the surface afterwards. If necessary, repeat the process until the desired result is achieved.

#### Important remarks

It is advised to always try out the product on a small test area. During the operation with **Glaspolijstpasta**, it is possible that polishing paths are formed. It is important during the polishing process that **Glaspolijstpasta** does not dry on the surface as this could cause the glass to break.

#### Quantity to use

60 à 70 m²/ltr

#### Packaging

750 ml

#### Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

#### Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Edition 21-02-2020



# Storage life

2 years after manufacturing in the original closed packaging.

# **Considerations**

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.

Edition 21-02-2020