

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ARTIPOX BT- COMP. A
Type of product : Epoxy resin.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rewah
Nijverheidsweg 24
B-2240 Zandhoven - Belgique-België
T +32 (0)3 4751414 - F +32 (0)3 4751094
info@rewah.com

1.4. Emergency telephone number

Emergency number : +32 (0)70 245 245

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
Repr. 2 H361
Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

GHS08

GHS09

Signal word (CLP) : Danger

Hazardous ingredients : reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); hydrocarbons, terpene processing by-products; nonylphenol

Hazard statements (CLP) : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H361 - Suspected of damaging fertility. (if swallowed).
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P273 - Avoid release to the environment.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	\geq 25	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Terpineol multiconstituent	(CAS-No.) 8000-41-7 (REACH-no) 01-2119553062-49	5 - 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319
hydrocarbons, terpene processing by-products	(CAS-No.) 68956-56-9 (EC-No.) 273-309-3 (REACH-no) 01-2119980606-28	5 - 25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE Not classified Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	1 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
nonylphenol substance listed as REACH Candidate substance listed in REACH Annex XIV (4-Nonylphenol, branched and linear, ethoxylated (substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, ethoxylated covering UVCB- and well-defined substances, polymers and homologues, which include any of the individual isomers and/or combinations thereof))	(CAS-No.) 25154-52-3 (EC-No.) 246-672-0 (EC Index-No.) 601-053-00-8 (REACH-no) 01-2119510715-45	1 - 5	Repr. 2, H361fd Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	1 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	0.1 - 1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	(C \geq 5) Skin Irrit. 2, H315 (C \geq 5) Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If experiencing respiratory symptoms: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Repeated exposure may cause skin dryness or cracking. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Irritating to eyes, respiratory system and skin.
Symptoms/effects after inhalation	: Exposure may produce cough, mucous, shortness of breath, chest tightness.

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after skin contact	: Red skin.
Symptoms/effects after eye contact	: Causes eye irritation.
Symptoms/effects after ingestion	: Abdominal pain.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid. and on exposure to temperature rise: pressure rise and possible bursting of container.
-------------	--

5.3. Advice for firefighters

Precautionary measures fire	: Avoid (reject) fire-fighting water to enter environment. Use water spray or fog for cooling exposed containers. All fire-fighting personnel must wear safety suits.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing, gloves and eye/face protection.
----------------------	--

6.1.2. For emergency responders

Emergency procedures	: Flammable liquids having a flash-point above 60 °C which are carried or handled over for carriage at or above their flash-point.
----------------------	--

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Restrict liquid from spreading over surface with floating screens if possible.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Waste to eliminate according to chemical waste law.
-------------------------	---

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Provide good ventilation in process area to prevent formation of vapour.
-------------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Handling and storage. National regulations.
--------------------	---

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Belgium	Local name	Xylène, isomères mixtes, purs
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
United Kingdom	Local name	Xylene, o-,m-,p- or mixed isomers

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)		
United Kingdom	WEL TWA (mg/m³)	220 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	441 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)
ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m³)	442 mg/m³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m³)	884 mg/m³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
Belgium	Local name	Ethylbenzène
Belgium	Limit value (mg/m³)	442 mg/m³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m³)	551 mg/m³
Belgium	Short time value (ppm)	125 ppm
Belgium	Remark (BE)	D
United Kingdom	Local name	Ethylbenzene
United Kingdom	WEL TWA (mg/m³)	441 mg/m³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m³)	552 mg/m³
United Kingdom	WEL STEL (ppm)	125 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
toluene (108-88-3)		
EU	Local name	Toluène
EU	IOELV TWA (mg/m³)	192 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	384 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Peau
Belgium	Local name	Toluène
Belgium	Limit value (mg/m³)	77 mg/m³
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m³)	384 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
United Kingdom	Local name	Toulene
United Kingdom	WEL TWA (mg/m³)	191 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	384 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

8.2. Exposure controls

Hand protection:

Wear suitable gloves resistant to chemical penetration.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Avoid contact with skin.

Respiratory protection:

An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits. Half mask with gas filter Type A filter material. CEN standards EN 136, 140 and 405 provide breathing masks and EN 149 and 143 provide recommendations to use filters. [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls:

Product may not flow into sewer or superficial water.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 160 - 245 °C
Flash point	: 141 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: > 200 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: ≈ 0.1 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: ≈ 1.1
Solubility	: Material insoluble in water. Material nearly insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: 1.9 cSt
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

strong oxidising compounds.

10.6. Hazardous decomposition products

Stable under normal conditions.

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

toluene (108-88-3)	
Additional information	LOAEC (inhalation, rat, vapour) 1.875 mg/l 6 months
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable.
Serious eye damage/irritation	: Causes serious eye damage. pH: Not applicable.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility. (if swallowed).
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

ARTIPOX BT- COMP. A	
Viscosity, kinematic	1.9 mm ² /s

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
---	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Insoluble in water.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

toluene (108-88-3)	
LC50 fish 1	5.5 mg/l Oncorhynchus kisutch
EC50 other aquatic organisms 1	3.78 mg/l Ceriodaphnia dubia
EC50 72h algae (1)	10 mg/l Skeletonema costatum
ErC50 (other aquatic plants)	84 mg/l Nitrosomonas sp.
NOEC (chronic)	1 mg/l Daphnia magna 21 d.
NOEC chronic fish	1.39 Oncorhynchus kisutch 40 d.

12.2. Persistence and degradability

ARTIPOX BT- COMP. A	
Persistence and degradability	Literature reports: not readily degradable in water.

toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
Biodegradation	86 % 20 d.

12.3. Bioaccumulative potential

ARTIPOX BT- COMP. A	
Bioaccumulative potential	Low bioaccumulation potential.

toluene (108-88-3)	
BCF fish 1	90 mg/kg Leuciscus idus (golden orfe)
Log Pow	2.73

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Component	
nonylphenol (25154-52-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information : Avoid release to the environment. .

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Forbidden through garbage can or sewerage, follow the next guidelines: 75/442/EG & 91/689/EG .

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / IATA

ADR	IATA
14.1. UN number	
3082	3082
14.2. UN proper shipping name	
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.
Transport document description	
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)), 9, III, (E)	UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
14.3. Transport hazard class(es)	
9	9
14.4. Packing group	
III	III
14.5. Environmental hazards	
Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available	

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : M6
Special provisions (ADR) : 274, 335, 601
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Orange plates

:



Tunnel restriction code (ADR)

: E

EAC code

: •3Z

- Air transport

Transport regulations (IATA)

: Not applicable.

PCA Excepted quantities (IATA)

: E1

PCA Limited quantities (IATA)

: Y964

PCA limited quantity max net quantity (IATA)

: 30kgG

PCA packing instructions (IATA)

: 964

PCA max net quantity (IATA)

: 450L

CAO packing instructions (IATA)

: 964

CAO max net quantity (IATA)

: 450L

Special provisions (IATA)

: A97, A158

ERG code (IATA)

: 9L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: nonylphenol (EC 246-672-0, CAS 25154-52-3)

Contains REACH Annex XIV substances:

Substance name	Authorisation number	Sunset date	REACH authorisation exemptions
4-Nonylphenol, branched and linear, ethoxylated (substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, ethoxylated covering UVCB- and well-defined substances, polymers and homologues, which include any of the individual isomers and/or combinations thereof) (EC 246-672-0, CAS 25154-52-3)		04/01/2021	

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information

: None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1

ARTIPOX BT- COMP. A

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT RE Not classified	Specific target organ toxicity (repeated exposure) Not classified
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.