

Specific cleaning and degreasing product for epoxy applications

Application

- Applied as a rinsing and cleaning product to clean the material which has been used to apply epoxy or polyurethane
- Used as well to degrease epoxy floors before additional finishing layers like polyurethane coatings are applied

Properties

- Strongly degreasing.
- Solvent based.
- Light flammable.

Directions

Work method

- As rinsing and clenaing product
 - Rinse and clean the material which has been used to apply epxoy or polyurethane.
 - Recuperate carefully the rinsing solvent into a suitable packaging and eliminate it legally.
- As degreasing product for epoxy floors
 - Soak a clean rag with the product and divide it over the floor.
 - Clean the floor afterwards with a new clean rag until the product is completely penetrated into the floor.
 - After complete evaporation of the product, further finishing layers can be applied.

Important remarks

- The product is a thinner which is classified as a light flammable and irritating substance. The necessary precautions can be found on the safety data sheet and must always be respected.

Technical characteristics

Specific gravity	+/- 0,81
Flash Point	- 4°C
Color	yellow

Quantity to use

In need of, depending of the application

Packaging

10 ltr and 25 ltr

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Edition 3-03-2020

1 of 2





Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

<u>Storage life</u>

Unlimited.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.

Edition 3-03-2020