

Acid product for neutralizing and eliminating salt efflorescences

Application

Is used to neutralize water soluble salts on affected masonry.

Properties

- Concentrate, to de diluted.
- Penetrates deeply into the surface.
- Neutralizing these salts therefore makes it possible to prevent them from causing any damage.
- Suitable for indoor and outdoor application.

Instructions

Preparation

- Window frames, glazing, metals, blue stone, etc. should be protected before treatment.
- Dilute **Saltremove** with water according to a ratio of 1:10.
- Any masonry requiring treatment should preferably be dry.

Work method

- Use a low pressure hand-held gun to apply the product to the surface requiring treatment.
- Allow the product to act for 15 up to 30 minutes.
- Then gently rinse the surface with water, in order to remove any salt efflorescences that may be present.
- You can also use a dry brush to remove the crystallised salts on the surface.

Important remarks

- The minimum temperature of the surface to be treated must be +5 °C.
- In case of severe pollution, you may need to repeat the treatment or reduce the dilution.
- In extreme cases the product can be used in its pure form.

Technical characteristics

Aspect	liquid
Density	+/- 1,1
pН	+/- 0,1

Application rate/Dosage

+/- 0,1 up to 0,2 ltr/m² (= quantity to use of the diluted product), depending of the subsoil

Packaging 10 ltr

Edition 22-12-2022



Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

2 years after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.

Edition 22-12-2022