

**Top-quality cover-all mat acrylate finish for interior use****Application**

- Very matt topcoat for interior walls and ceilings
- Can be applied on plaster, plasterboard sheets, concrete, brick etc, ..

**Properties**

- Washable
- Highly scrub-resistant (class 1)
- Super-matt look.
- Seamless finish.
- Exceptionally fluid.
- Good coverage.
- Easy to work with.
- Does not splash.
- Combines ideally with Estetik Prim
- Available in base paints.

**Directions****Preparation**

- The base must be clean, dry and intact.
- Clean off any dust and grease thoroughly with Omniclean.
- Sand off and clean any previously painted substrates.

**Work method**

Brush or roller	non-diluted
Recommended roller	polyamide (no micro fibre)
Airless	0,017"-0,019"; 200-220 bar (160 bar with FFLP tip Graco)
Ambient temperature	minimum 10°C
Relative humidity	maximum 80%

**System structure**

- **New substrates**
  - o The base must be clean, sturdy and dry.
  - o Remove dust and grease thoroughly with Omniclean.
  - o Pretreat with 1 layer Estetik Prim, diluted with 5% water.
  - o Finish with 1-2 coats of **Estetik Easy Mat** in the required final color. (only with light colors, with most colors 1 layer will suffice.)
- **Previously painted substrates**
  - o Degrease thoroughly with Omniclean.
  - o Sand well until mat.
  - o Pre-treat with Estetik Prim, non-diluted (5% dilution is permitted).
    - For sealing water-soluble stains (nicotine, rust, ink), pre-treat with 1 coat of Estetik Isolprim.

- Finish with 1-2 coats of **Estetik Plafond** in the required final color. (only with light colors, with most colors 1 layer will suffice.)

**Drying times**

Dust-dry                      after 1 hour  
Can be painted over      after 4 hours

**Cleaning**

The tools can be cleaned with water immediately after use.

**Technical characteristics**

Form	hybrid of high-quality acrylates
Colour	rutile titanium dioxide and specific good-quality fillers
Solvent	water
Specific weight	+/- 1,42 kg/l
Brookfield	(4RPM / spindel 4): 20-25%
Content of solid substance	50-55 w%
VOC-EU threshold value	EU threshold value for this product (catA/h): 30 g/l (2010). This product contains maximum 30 g/l VOC.
Scrub resistance	classification 1 (NBN EN 13300)

**Colors**

White and light colors on the coloring machine.

**Gloss level**

Mat (< 1GU / 85°C)

**Quantity to use**

0,10 – 0,15 ltr/m<sup>2</sup>/per layer depending on the base

**Packaging**

1L, 2,5L, 5L, 10L

**Safety information – Transport – Handling and storage - Waste**

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

**Transport and storage**

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Uitgave 11-09-2025

2 van 3

**Storage life**

1 year after manufacturing in the original closed packaging.

**Considerations**

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.